

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/072632 A1

(51) International Patent Classification⁷: **A61B 17/70**

(21) International Application Number:
PCT/IB2005/000341

(22) International Filing Date: 21 January 2005 (21.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04 00745 27 January 2004 (27.01.2004) FR
60/554,416 19 March 2004 (19.03.2004) US
04 11266 22 October 2004 (22.10.2004) FR

(71) Applicant (for all designated States except US): **MEDICREA INTERNATIONAL** [FR/FR]; 24 Porte du Grand Lyon, F-01700 NEYRON (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SOURNAC, Denys**


[FR/FR]; 345 Montée de Bellevue, F-01600 REYRIEUX (FR). **CAFFIERO, Jean-Philippe** [FR/FR]; 12 rue du Commandant Faurax, F-69006 LYON (FR). **CARLIER, François** [FR/FR]; Allée de Colveu, F-44352 GUERANDE (FR).

(74) Common Representative: **MEDICREA INTERNATIONAL**; 24 Porte du Grand Lyon, F-01700 NEYRON (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: VERTEBRAL OSTEOSYNTHESIS EQUIPMENT



(57) Abstract: This vertebral osteosynthesis equipment includes bony anchoring members, such as pedicular screws (1), one or two linking rods (2), intended to be connected to these anchoring members, and connection assemblies (6, 3) of this or these rods (2) to these anchoring members, at least one of these anchoring members (1) being of the "polyaxial" type, i.e. including a connection part (6) articulated with respect to a base portion (5) intended to be attached to the vertebrae. According to the invention, said "polyaxial" anchoring element (1) comprises a flexible junction portion (7) connecting said connection part (6) and said base portion (5), this flexible junction portion (7) providing the desirable joint of this connection part (6) with respect to the base portion (5).



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

VERTEBRAL OSTEOSYNTHESIS EQUIPMENT

The present invention concerns a vertebral osteosynthesis equipment.

A vertebral osteosynthesis equipment comprises generally bony anchoring members, such as pedicular screws, forceps or hooks, one or two
5 linking rods, intended to be linked to these anchoring members, and connection parts of this or these linking rods to these anchoring members. The equipment may also contain crosslinks adjustable in length, which connect transversally two parallel linking rods to maintain these rods with respect to one another.

10 In a type of existing equipment, each anchoring element may include a proximal threaded stud whereon may be screwed a nut and each connection part may contain a rounded portion intended to surround a linking rod and two parallel wings drilled with holes. These wings are intended to be engaged on said proximal threaded stud and to be clamped, by means of this nut, against
15 a bearing surface provided on the anchoring element, this clamping causing in turn the clamping of said rounded portion around the linking rod and thereby ensuring the longitudinal immobilisation of this rod with respect to the anchoring element.

In another type of existing equipment, each anchoring element may be
20 "tulip-shaped", i.e. include a head wherein is provided a transversal passage for receiving a linking rod.

The anchoring members may be of "polyaxial" type, i.e. enable, before clamping, a joint of the connection part (proximal threaded stud or "tulip-shaped" head) with respect to the base portion of the anchoring element,
25 intended to be inserted in the bone. This joint facilitates the assembly of the linking rods to the anchoring members.

In the existing "polyaxial" anchoring members, the joint is realised in the form of a ball joint with spherical portions, either by providing a sphere at the distal end of a threaded proximal stud and a cavity in said base portion, this
30 cavity receiving the sphere of the stud and being closed at the proximal portion

to retain this sphere, or by providing a sphere at the proximal end of the base portion and a cavity corresponding to the bottom of the "tulip-shaped" head. The documents US 5,882,350 or WO 00/15125 illustrate such materials.

5 The shortcoming of this type of joint lies in enabling only limited bottoming of the connection part, taking into account the stop of this part against the base portion at the edge closing the cavity receiving the sphere. This limited bottoming may compromise in certain cases the placement of a rod on anchoring members. Moreover, the contact surface of the sphere with said edge is restricted and the clamping of the rod generates relatively
10 significant axial tension on this edge, which is not optimal from a mechanic viewpoint. Besides, the repeated stresses inflicted to the equipment once implanted, resulting from the movements of the patient, generate repeated frictions of the sphere against said edge, which leads to an undesirable risk of diffusion of metal particles in the organism.

15 Besides, the existing vertebral osteosynthesis equipment is intended to immobilise two vertebrae with respect to one another, to eliminate any relative movement of these vertebrae, or to restore the adequate position of a vertebra with respect to the other. For the realisation of this immobilisation, this equipment is designed for a perfectly rigid assembly of the linking rods with
20 the anchoring members.

This rigid assembly may however not be desirable in all cases. It leads in particular to the application of significant stresses to anchoring bony zones of said anchoring members, as well as to increased stresses at vertebral joints situated of both sides of the vertebral segment treated, which may lead to
25 degenerescences of these joints. Besides, this rigid assembly is not adapted to the treatment of non-degenerative affections, notably to the treatment of scoliosis in younger patients.

The purpose of the present invention is to remedy all these shortcomings.

Its main object is hence to provide a vertebral osteosynthesis equipment comprising at least one polyaxial anchoring element, wherein the connection part has a significant bottoming with respect to the base portion of the anchoring element intended to be attached to the bone, and wherein the risk
5 of diffusion of metal particles in the organism is significantly reduced with respect to an existing equipment.

Another object of the invention is to provide a vertebral osteosynthesis equipment enabling non-rigid assembly, possibly flexible assembly, of the linking rods with the anchoring members, with possible dampening effect of
10 the movement of the mobile parts.

An additional object of the invention is to provide a vertebral osteosynthesis equipment enabling such non-rigid assembly, possibly flexible assembly, having a mobile portion whereof the localisation is close to the conditions of anatomic movements.

15 An additional object of the invention is to provide a vertebral osteosynthesis equipment having small space requirements in order to minimise the interventions necessary to realise the implantation.

The equipment concerned includes, in itself, bony anchoring members, such as pedicular screws, forceps or hooks, one or two linking rods, intended
20 to be connected to these anchoring members, and connection assemblies of this or these rods to these anchoring members, at least one of these anchoring members being of the "polyaxial" type, i.e. including a connection assembly articulated with respect to a base portion intended to be attached to the bone.

25 According to the invention, said "polyaxial" anchoring element comprises a junction portion connecting a portion of said connection assembly and said base portion, this junction portion having a flexible structure providing the desirable joint of this connection assembly with respect to the base portion.

The joint of the connection assembly is thus not a ball joint with spherical
30 portions, but provided by the single flexion of said junction portion. The

bottoming of the connection assembly may be quite significantly greater than that of a connection assembly of an existing anchoring element. Moreover, the axial tension imparted between the connection assembly and the base portion after assembly applies to the junction portion globally and not to a restricted surface of a portion of a joint, as according to the previous technique.

The absence of contact of portions of joint on restricted surfaces enables to reduce quite significantly, possibly to eliminate, the risk of diffusion of metal particles in the organism, and of wear of the material. There results the possibility of allowing flexibility of said junction portion after implantation, enabling thus non-rigid assembly, possibly flexible assembly, of the linking rods with the anchoring members.

The junction portion enables several degrees of multidirectional movements of said connection assembly with respect to the base portion, in translation as well as in pivoting motion.

Besides, the joint according to the invention is significantly less cumbersome than a joint according to the previous technique, which enables not only to minimise the interventions to realise for the implantation but also to localise this joint in order to come as close as possible to the conditions of anatomic movements.

According to a possibility, the junction portion is formed by a part distinct from the part of said connection assembly and of the base portion. The junction portion may then notably be composed of a rod of flexible material.

According to another possibility, the junction portion is composed of an extension of the base portion or of said part of the connection assembly, made flexible by an appropriate shape and/or by slots or recesses. This extension may for instance have a tubular structure and exhibit a helicoid slot, or may exhibit stepped radial recesses, preferably offset angularly.

The junction portion and the links of said part of said connection assembly and of said base portion may be designed so that said part of said

connection assembly and said base portion are never in contact with one another.

This absence of contact eliminates the risk of diffusion of metal particles in the organism.

- 5 Alternately, the junction portion is slightly stretchable longitudinally and means are provided to stretch this junction portion slightly longitudinally, enabling to space the surfaces away from one another whereas said part of said connection assembly and the base portion contact one another.

- 10 These surfaces of said part and of the base portion may be shaped to guide the movement of joint of this part with respect to the base portion. It may notably concern surfaces in portions of a sphere, respectively concave and convex, and provided coaxially to said junction portion.

- 15 These surfaces enable thus, when reducing vertebrae for osteosynthesis, to guide the movement of the part of said connection assembly with respect to the base portion in order not to subject the junction portion to excessive transversal stresses.

Along the same line, these same surfaces of the part of said connection assembly and of the base portion may be bordered by lateral bearing surfaces, enabling lateral wedging of said part with respect to the base portion.

- 20 Preferably, said anchoring element of "polyaxial" type comprises at least one part or a portion of part with elastically deformable structure, placed after assembly, between a part of the connection assembly and said base portion, this part or portion of part with elastically deformable structure enabling mobility of the connection assembly, and hence of the linking rod, with respect to the base portion, with a dampening effect.

- 25 Thus, in the equipment according to the invention, the connection assembly is not immobilised with respect to the base portion after assembly but may, relative to the elastic deformability of said part or portion of part, have a certain clearance with respect to the base portion in order to authorise limited movements of the vertebrae. The stresses imparted by the anchoring
- 30

element on the anchoring bony zones are thus notably reduced, as well as the risks of excessive stresses at vertebral joints situated on both sides of the vertebral segment treated.

5 The invention will be better understood, and other characteristics and advantages thereof, will appear with reference to the appended schematic drawing, representing, for non-limiting exemplification purposes, several possible embodiments of parts contained in the equipment affected.

Figure 1 is an axial sectional view of the different elements forming an anchoring element and a connection assembly contained in this equipment,
10 according to a first embodiment;

Figure 2 is a lateral view of this anchoring element, of this connection assembly and of a linking rod, after assembly;

Figure 3 is a sectional view of these anchoring element, connection assembly and linking rod along the line III-III of Figure 2;

15 Figure 4 is a top view of these anchoring element, connection assembly and linking rod;

Figures 5 to 7 are perspective exploded, side and sectional views, respectively of the anchoring element, of the connection assembly and of the linking rod according to a second embodiment, along the line VII - VII of Figure
20 6;

Figures 8 to 10 are similar views of the anchoring element, of the connection assembly and of the linking rod according to a third embodiment, and

Figures 11 and 12 are views of the anchoring element, of the connection
25 assembly and of the linking rod according to a fourth embodiment, respectively in perspective before assembly and as a sectional view along the axis of the anchoring element.

By simplification, the portions or elements described for the first embodiment, which can be found identically or similarly in the other

embodiments, will be designated by the same numeric references and will not described further.

Figures 2 to 4 represent a polyaxial pedicular screw 1, a rod 2 for linking several of these screws 1, a yoke 3 for connecting this rod 2 to one of these screws 1 and a nut 4 enabling to assemble the linking rod 2 to this screw 1.

As shown more particularly on Figure 1, the screw 1 comprises a base part 5 in the form of a screw, a proximal threaded stud 6, an elongated element 7, for joining the base part 5 and the stud 6, a screwable plug 8 for assembling the element 7 to the base part 5 and a crimpable ring 9 for assembling the element 7 to the stud 6. The screw 1 comprises also a part 10 with elastically deformable structure and a ring 11 bearing against this part 10.

The stud 6, the yoke 3, the nut 4, the part 10 and the ring 11 form a connection assembly of a linking rod 2 to a base portion 5.

The base part 5 is metallic, notably made of titanium, as well as the stud 6, the rod 2, the yoke 3, the nut 4, the plug 8, the crimpable ring 9 and the ring bearing 11. It comprises a threaded cylindrical portion 15 enabling its insertion in the pedicle of a vertebra, and a widened head 16 intended to bear against this pedicle.

This head 16 comprises a cylindrical upper cavity 17, liable to receive the part 10 with a shrink-fit, a cylindrical intermediate cavity 18 with concave spherical bottom, liable to receive the base of the stud 6, and a lower bore 19, liable to receive an end of the element 7, these cavities 17, 18 and bore 19 being coaxial to the axis of the base portion 5.

The head 16 also comprises a tapered transversal perforation 20, emerging in the bore 19. As appears on Figure 3, the plug 8 is intended to be screwed in the perforation 20 in order to clamp the element 7 in the bore 19 and thus ensure the assembly of this element 7 with the base portion 5.

The stud 6 comprises an axial bore 22 liable to be traversed by the element 7, a proximal thread 23 and a wider base 24 with convex spherical

distal face, whereas this base 24 may be received with a shrink-fit, but with possibility of movement, in the cavity 18.

The element 7 may notably be formed of braided polyester wires. After its engagement through the bore 22, this element 7 receives the ring 9, which is crimped thereon in order to maintain the base 24 in the cavity 18. The surplus portion of the element 7 is then cut beyond the ring 9.

The part 10 may notably be of silicon or of PMMA. It comprises an axial perforation 25 enabling its engagement on the stud 6, this bore 25 being flared at its lower portion to promote the bottoming of the stud 6 with respect to the base portion 5.

The bearing part 11 comprises an upper portion 26 drilled with a tapered bore 27 enabling to screw it on the stud 6 and a wider lower portion 28, delineating a lower cylindrical cavity 29 liable to receive the part 10 with a shrink-fit.

The part 10 is thus intended to be engaged on the stud 6 until it rests against the bottom of the cavity 17 and the part 11 is intended to be screwed on the stud 6 in order to clamp the part 10 therebetween and the base portion 5, independently of the clamping realised by the nut 4. The part 11 may be clamped in a controlled fashion, for instance by means of a torque wrench, according to the degree of dampening effect requested of the movement of the stud 5, relative to the characteristics of the patient (condition of the intervertebral disks, degree of vertebral instability, weight). The effect of this clamping is also to cause slight stretching of the element 7, which enables to move the convex face of the base 24 from the bottom concave of the cavity 18.

There results that the multidirectional movement of the stud 6 with respect to the base portion 5 is possible thanks to the sole flexibility of the element 7, according to a bottoming important, without any restricted bearing zone of the stud 6 against an edge of the base portion 5, and without any

substantial friction of the adjacent surfaces of the stud 6 and of the base portion 5.

The linking rod 2 is cylindrical and exhibits such rigidity that it enables to maintain several vertebrae relative to one another. This rod 2 is however
5 deformable in order to be shaped relative to the vertebral correction to be carried out.

The yoke 3 comprises a rounded portion 30 intended to surround the linking rod 2 and two parallel lateral wings 31 drilled with holes 32 for the engagement of the yoke 3 on the stud 6. These wings 31 are mutually distant
10 so that, in a spaced apart position, the rod 2 may be inserted and may slide in the portion 30, and, in a closing-in position provided by clamping the nut 4, they clamp the portion 30 around the rod 2, immobilising said rod with respect to the yoke 3.

As shown on Figure 1, each wing 31 exhibits a cavity 33, 34 on its outer
15 face, intended for receiving the nut 4 and the bearing ring 11, respectively.

In practice, the number of screw 1 necessary to the treatment to realise is implemented in the pedicles of the vertebrae affected, then the yokes 3, with the rod 2 engaged in the portions 30, are placed on the studs 6.

The significant bottoming of the studs 6 enables to facilitate quite notably
20 this placement of the yokes 3 on its studs 6. During this operation, while the vertebrae are reduced towards their osteosynthesis position, the heads 16 of the base portions 15 maintain transversally the bases 24 of the studs 6 and eliminate thus any risk of applying to the elements 7 excessive transversal stresses.

25 The nuts 4 are then clamped to bring the branches 31 together and thus clamp the rods 2 in the portions 30 of the yokes 3.

Figures 5 to 7 represent another embodiment of the osteosynthesis equipment according to the invention, also including a base part 5, a proximal threaded stud 6, a yoke 3 and a nut 4.

In such a case, the base part 5 comprises a proximal tubular extension 40 wherein is provided a helicoid slot 41.

This extension 40 is also drilled with two transversal coaxial holes 42 and the stud 6 comprises a transversal hole 43 facing, during the assembly of the stud 6 and of the base portion 5, these holes 42, whereas the holes 42, 43 may then receive a pin 44 pushed therethrough.

The slot 41 enables to confer the extension 40 the required flexibility to enable the stud 6 to bottom with respect to the base portion 5 and to enable a non-rigid assembly of a linking rod 2 to a base portion 5.

The yoke 3 and the nut 4 may be identical to those described previously or, as is represented, the nut 4 may exhibit an outer peripheral face in portion of a sphere and the yoke 3 may exhibit an upper cavity 33 of corresponding shape, wherein the nut 4 is totally engaged after complete screwing, as shown on Figure 7.

Figures 8 to 10 represent another embodiment of the osteosynthesis equipment according to the invention, also including a base portion 5 with proximal tubular extension 40, a proximal threaded stud 6, a yoke 3 and a nut 4.

In such a case, the proximal tubular extension 40 comprises stepped radial recesses 45, whereas each recess is provided on slightly less than half the circumference of the extension 40 and is provided with an angular offset with respect to the recesses 45 of the adjacent stages. These recesses 45 enable to delineate spaces authorising transversal deformation of the extension 40 in an "accordion"-like fashion, conferring this extension 40 the required flexibility.

The assembly of the stud 6 to the extension 40 may be realised by means of a pin as described previously, or, as represented, by screwing and gluing a threaded base of the stud 6 in the bore of the extension 40, which is also tapered.

The proximal threaded stud 6 may contain an upper stud 46 for screwing an extension (not represented) enabling to facilitate the descent of the yoke 3 - linking rod 2 assembly on the stud 6 when implanting the equipment.

Figures 11 and 12 represent a "tulip"-type screw 1, i.e. whereof the head 50 is widened and exhibits a transversal housing 51 for receiving a linking rod 2. This head 50 exhibits an axial tapered bore 52 provided in facing walls delineated by the transversal housing 51 and receives a nut 4 for locking the linking rod 2 in the housing 51.

In such a case, the base of the head 50 also comprises stepped radial recesses 45, whereas each recess is provided on slightly less than half the circumference of the head 50 and is provided with an angular offset with respect to the recesses 45 of the adjacent stages. These recesses 45 enable, as described previously, to delineate spaces authorising transversal deformation of the head 50 in an "accordion"-like fashion, conferring this head 50 the required flexibility.

As appears from the foregoing, the invention provides a vertebral osteosynthesis equipment wherein a part 6, 50 of the connection assembly has a significant bottoming with respect to the base portion 5 of the anchoring element 1 intended to be attached to the bone and wherein the risk of diffusion of metal particles in the organism is significantly reduced with respect to an existing equipment.

This vertebral osteosynthesis equipment enables moreover non-rigid assembly, possibly flexible assembly, of the linking rods 2 with the anchoring members 1, with possible dampening effect of the movement of the mobile parts.

Besides, this equipment has a mobile portion whereof the localisation is close to conditions of anatomic movements, and has small space requirements in order to enable to minimise the interventions necessary to realise the implantation.

It goes without saying that the invention is not limited to the embodiment described above for exemplification purposes but it extends to all the embodiments covered by the claims appended thereto.

In particular, the expression "connection part" should be understood in a
5 wide meaning: it may be a proximal threaded stud 6 or a connection part in the form of a "tulip", i.e. including a housing for receiving a linking rod.

Similarly, the expression "base portion" 5 should be understood as any structure enabling the attachment of the anchoring element 1 with one vertebra, notably in the form of pedicular screw, forceps or hook.

CLAIMS

1 – vertebral osteosynthesis equipment comprising bony anchoring members, such as pedicular screws (1), forceps or hooks, one or two linking rods (2), intended to be connected to these anchoring members, and
5 connection assemblies (6, 3, 4, 10, 11 ; 40, 50, 4) of this or these rods (2) to these anchoring members, at least one of these anchoring members (1) being of the "polyaxial" type, i.e. including a connection assembly (6, 3, 4, 10, 11 ; 40, 50, 4) articulated with respect to a base portion (5) intended to be attached to the vertebra ;

10 Equipment characterized in that said "polyaxial" anchoring element (1) comprises a junction portion (7, 40) connecting a portion (6, 50) of said connection assembly (6, 3, 4, 10, 11 ; 40, 50, 4) and said base portion (5), this junction portion having a flexible structure providing the desirable joint of this connection assembly (6, 3, 4, 10, 11 ; 40, 50, 4) with respect to the base
15 portion (5).

2 – Equipment according to claim 1, characterized in that the junction portion is formed by a part (7) distinct from the part (6, 50) of said connection assembly (6, 3, 4, 10, 11 ; 40, 50, 4) and of the base portion (5).

3 – Equipment according to claim 2, characterized in that the junction
20 portion may then notably be composed of a rod (7) of flexible material.

4 – Equipment according to claim 1, characterized in that the junction portion is composed of an extension (40) of the base portion (5) or of said part (50) of the connection assembly, made flexible by an appropriate shape and/or by slots (41) or recesses (45).

25 5 – Equipment according to claim 4, characterized in that the extension (40) may for instance have a tubular structure and exhibit a helicoid slot (41), or may exhibit stepped radial recesses (45), preferably offset angularly.

6 – Equipment according to any claims 1 to 5, characterized in that the junction portion and the links of said part of said connection assembly and of

said base portion may be designed so that said part of said connection assembly and said base portion are never in contact with one another.

7 – Equipment according to any claims 1 to 5, characterized in that the junction portion (7) is slightly stretchable longitudinally and means (6, 9, 3, 4, 10, 11) are provided to stretch this junction portion (7) slightly longitudinally, enabling to space the surfaces away from one another whereas said part (6) of said connection assembly and the said base portion (5) contact one another.

8 – Equipment according to any claims 1 to 7, characterized in that surfaces by which said part (6) of said connection assembly and the said base portion (5) contact one another, may be shaped to guide the movement of joint of this connection part (6) with respect to the base portion (5).

9 – Equipment according to claim 8, characterized in that said surfaces of the part (6) of said connection assembly and of the base portion (5) may be bordered by lateral bearing surfaces, enabling lateral wedging of said part (6) with respect to the base portion (5).

10 – Equipment according to any claims 1 to 9, characterized in that said anchoring element (1) of "polyaxial" type comprises at least one part or a portion of part (10) with elastically deformable structure, placed after assembly, between a part (11) of the connection assembly and said base portion (5), this part or portion of part (10) with elastically deformable structure enabling mobility of the connection assembly, and hence of the linking rod (2), with respect to the base portion (5), with a dampening effect.




FIG. 1

2 / 4

FIG. 4





FIG. 2




FIG. 3

3 / 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB2005/000341

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 946 458 A (HARMS ET AL) 7 August 1990 (1990-08-07) column 3, line 4 - line 27; figures 1,2	1,2,6,10
Y	-----	4,5,8,9
Y	WO 03/047441 A1 (MATHYS MEDIZINALTECHNIK AG; STUDER, ARMIN) 12 June 2003 (2003-06-12) figures 3-5	4,5
Y	WO 03/068088 A (CROSS MED PROD INC) 21 August 2003 (2003-08-21) page 5, line 3 - page 6, line 9; figures 1,2	8,9
	----- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

13 May 2005

Date of mailing of the international search report

24/05/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ducureau, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB2005/000341

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 882 350 A (RALPH JAMES D ET AL) 16 March 1999 (1999-03-16) column 6, line 32 - line 39; figure 5 column 7, line 4 - line 13; figure 7 column 8, line 7 - line 45; figures 9,10 -----	1
X	WO 00/15125 A (SYNTHES AG ; BRACE MICHAEL (US); SYNTHES USA (US); LANGE ERIC (US)) 23 March 2000 (2000-03-23) page 4, paragraph 8 - page 5, paragraph 3; figures 1,2 -----	1
A	FR 2 827 498 A1 (FORTIN FREDERIC) 24 January 2003 (2003-01-24) abstract; figures 1-3 -----	1,3
A	FR 2 697 742 A1 (BIOMAT) 13 May 1994 (1994-05-13) page 11, line 14 - page 12, line 9; figure 1 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB2005/000341

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4946458	A	07-08-1990	DE 3614101 C1	22-10-1987
			AT 82484 T	15-12-1992
			CA 1328591 C	19-04-1994
			DE 3782678 D1	24-12-1992
			EP 0242708 A2	28-10-1987
			ES 2035826 T3	01-05-1993
			JP 1802142 C	26-11-1993
			JP 5008011 B	01-02-1993
			JP 62277954 A	02-12-1987
			KR 9506929 B1	26-06-1995
WO 03047441	A1	12-06-2003	AU 2002218099 A1	17-06-2003
			AU 2002242566 A1	17-06-2003
			BR 0117188 A	09-11-2004
			BR 0214584 A	03-11-2004
			CA 2469005 A1	12-06-2003
			CA 2469008 A1	12-06-2003
			WO 03047442 A1	12-06-2003
			CZ 20040691 A3	16-02-2005
			EP 1450707 A1	01-09-2004
			EP 1450708 A1	01-09-2004
			NZ 533300 A	25-02-2005
			NZ 533301 A	24-03-2005
			US 2005056979 A1	17-03-2005
			US 2005065514 A1	24-03-2005
WO 03068088	A	21-08-2003	US 2004006342 A1	08-01-2004
			US 2003163133 A1	28-08-2003
			AU 2003210964 A1	04-09-2003
			EP 1474053 A1	10-11-2004
			WO 03068088 A1	21-08-2003
US 5882350	A	16-03-1999	US 5669911 A	23-09-1997
			US 5520690 A	28-05-1996
			US RE37665 E1	16-04-2002
			AT 250393 T	15-10-2003
			AU 714659 B2	06-01-2000
			AU 5539796 A	30-10-1996
			CA 2216955 A1	17-10-1996
			DE 69630117 D1	30-10-2003
			DE 69630117 T2	09-06-2004
			EP 1364623 A1	26-11-2003
			EP 0828459 A1	18-03-1998
			JP 3497865 B2	16-02-2004
			JP 11503351 T	26-03-1999
			US 2002045899 A1	18-04-2002
			WO 9632071 A1	17-10-1996
			US 5531746 A	02-07-1996
			US 5643265 A	01-07-1997
			US 5647873 A	15-07-1997
			US 5607426 A	04-03-1997
			US 5876402 A	02-03-1999
			US 5725588 A	10-03-1998
			US 5690630 A	25-11-1997
			US 5817094 A	06-10-1998
WO 0015125	A	23-03-2000	AU 751174 B2	08-08-2002
			AU 5404799 A	03-04-2000

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/IB2005/000341

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0015125	A	CA 2343327 A1	23-03-2000
		WO 0015125 A1	23-03-2000
		EP 1109502 A1	27-06-2001
		JP 2002524188 T	06-08-2002
		US 6187005 B1	13-02-2001
		ZA 200100673 A	28-08-2001
FR 2827498	A1	24-01-2003	
		CA 2453989 A1	30-01-2003
		EP 1408860 A1	21-04-2004
		WO 03007828 A1	30-01-2003
FR 2697742	A1	13-05-1994	
		AT 146064 T	15-12-1996
		CA 2109457 A1	07-05-1994
		DE 69306536 D1	23-01-1997
		DE 69306536 T2	28-05-1997
		EP 0596788 A1	11-05-1994
		ES 2096249 T3	01-03-1997
		GR 3022754 T3	30-06-1997
		JP 2666683 B2	22-10-1997
		JP 6165789 A	14-06-1994
		US 5380325 A	10-01-1995